

**TECHMARK**

Equal Partners

# WATER HEATERS

Perfect shower,  
that relax and  
rejuvenate you

**CAPACITY**  
**10 to 100**  
**LITRES**



Adjustable  
Knob

Copper  
Element

Anti Corrosive Vitreous  
Enamel Coated Tank

Efficient  
Thermal Insulation

8 Bar  
Pressure

## TANKLESS WATER HEATER

3.5KW/4.5KW/5.5KW/6.5KW/8.5KW



Aesthetic Design with Glass Finish Body

Digital Display

In-built Leakage Protection Device

Sensor Fault Protection

Rated Voltage	AC 220V / 50Hz	Pipe Connection	1/2" BSP
Highest Temperature Setting	52-55°C	Earth Leakage Circuit Breaker	40A
Operating Water Pressure	0.02~0.6MPa	Dry Heat Protection	When Temp Achieves 85-93
Water Proof Degree	IPX4	Lowest Water Flow Range	0.92/Min
Rated Pressure	0.6MPa	Phase	Single
Protection Against Electric Shock	Class 1	Relative Humidity	Above 95% (Indoor Temperature 25°C)
Over Temp Protection	55°C	Using Environment Temp	0-50°C

MODEL	3.5kW	4.5kW	5.5kW	6.5kW	8.5W
Rated Power (W)	3500	4500	5500	6500	8500
Current (A)	16	20	25	30	32
Wire Gauge (mm <sup>2</sup> )	3×2.5	3×2.5	3×4	3×6	3×6
Dimensions (mm)	203×137×53	203×137×53	397×257×65	397×257×65	397×257×65
Weight (Kg)	1.64	1.64	3.96	3.96	3.96

## STORAGE WATER HEATER

50L / 80L / 100L



Heating Power	1.2/1.5W
Heating Element	Copper
Control Type	Manual
Rated Current	5.22 Amp
Star Rating	5 Star
Control	Combistar 280mm

Outer Body	Metal Body
Top and Bottom	Plastic (PP)
Safety Valve Pressure	8 BAR
Knob	Yes
MG Anode Rod	Yes

Tank Capacity	50L	80L	100L
Heating Time $\Delta$ 20°C	48 min	1h 17m	1h 36m
Product Size (mm) (DxB) (Vertical)	496×615	496×860	496×1014
Product Size (mm) (DxB) (Horizontal)	496×615	496×860	496×1014
Tank Diameter (mm)	405	405	405
Product Net Weight (Kg.)	16	22	25
Container Load 40ft (HC)	336	252	214

## STORAGE WATER HEATER

10L / 15L / 25L



Heating Power	2W
Heating Element	Copper
Control Type	Manual
Rated Current	5.22 Amp
Star Rating	5 Star
Control	Capillary Thermostat /Cut out

Outer Body	Metal Body
Top and Bottom	Plastic (PP)
Safety Valve Pressure	8 BAR
Knob	Yes
MG Anode Rod	Yes

Tank Capacity	10L	15L	25L
Heating Time $\Delta$ 20°C	20 min	30 min	1h 36m
Product Size (mm) (DxB) (Vertical)	323×440	323×550	368×601
Product Size (mm) (DxB) (Horizontal)	320×487	320×607	320×870
Tank Diameter (mm) (Vertical)	260	260	306
Tank Diameter (mm) (Horizontal)	225	225	225
Product Net Weight (Kg.) (Vertical)	8.8	10.4	13.12
Product Net Weight (Kg.) (Horizontal)	8.8	9.23	13
Container Load 40ft (HC)	960	768	560